



Eteng Company Limited

7#309, Longteng Blvd, National Economy
Development District, Longteng South Road,
Longyan City, Fujian, P.R China 364000

T:0086-597-2992225
info@etengcn.com

ET-350 Thermal pad

测试项目 Test Item	单位 Unit	数值 Data	测试标准 Test Method
颜色 Color	-----	Gray white	Visual
厚度 Thickness	mm	0.2-5mm	ASTM D374
规格 Spec	mm	200×400	ASTM D1204
密度 Density	g/cc	2.0—2.2	ASTM D792
硬度 Hardness	Shore 00	25±5	ASTM D2240
撕裂强度 Tensile Strength	KN/m	2.3	ASTM D412
延伸率 Elongation	%	95 60	ASTM D412
击穿电压 Breakdown Voltage	Kv/mm	≥4.0	ASTM D149
体积电阻率 Volume Impedance	Ω.cm	1.7×10 ¹³	ASTM D257
耐温范围 Continuous Use Temp	°C	-40~220	EN344
重量损失 Weight Damnify	%	≤1	@200°C 200H
防火性能 Flame Rating	-----	94V-0	UL 94
热阻率 Thermal Resistance	°C/W	0.25	ASTM D5740
导热系数 Thermal Conductivity	W/m.k	3.50	ASTM E 1461-01