



Eteng Company Limited
7#309,Longteng BVLD, Dongxiao National Economy
Development District ,Longteng South Road,
Longyan City, Fujian 364000
T:0086-597-2992225
info@etengcn.com

ET-7050 EMI Shielding Copper Foil Tape

Product Description

Part number ET-7050 is **0.05mm** thickness pure copper foil coating with conductive acrylic adhesive or non-conductive acrylic adhesive.

The purity of copper foil is higher than 99.95%, and its function is to eliminate electromagnetic(EMI) interference, isolation of electromagnetic waves on the human body injury, avoid unwanted voltage and current without affecting functionality.

we can supply hundreds of width and length. below catalogue is limited.
please feel free to contact us if you need other size

Width: Min.width is 3mm,Max. width of copper foil is 310mm or 380mm

Length: hundreds of length

Acrylic adhesive: Conductive or non conductive Acrylic adhesive

Diameter of core : 38mm and 76mm

Part number	Acrylic adhesive	Copper foil Thickness	Total thick	Width	Length(meter)
ET-7050-003	Conductive or non conductive	0.05mm	0.09mm	3mm	3m,6m,25m,33m,50m
ET-7050-006	Conductive or non conductive	0.05mm	0.09mm	6mm	3m,6m,25m,33m,50m
ET-7050-010	Conductive or non conductive	0.05mm	0.09mm	10mm	3m,6m,25m,33m,50m
ET-7050-025	Conductive or non conductive	0.05mm	0.09mm	25mm	3m,6m,25m,33m,50m
ET-7050-050	Conductive or non conductive	0.05mm	0.09mm	50mm	3m,6m,25m,33m,50m
ET-7050-100	Conductive or non conductive	0.05mm	0.09mm	100mm	3m,6m,25m,33m,50m
ET-7050-310	Conductive or non conductive	0.05mm	0.09mm	310mm	3m,6m,25m,33m,50m
ET-7050-380	Conductive or non conductive	0.05mm	0.09mm	380mm	3m,6m,25m,33m,50m